

OSO Hotwater - ErP information

26.05.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)								
OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Heat-up time Δt 65°C [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]	Volume [L]	Heat loss [W]	Rating ERP	Profile ERP
Domestic products - Direct electric													
8 000 721	W 30 - 2 kW/1x230V	Wallsmart	430	490	1	66	30	625	65	28	27	D	S
8 000 722	W 50 - 2 kW/1x230V	Wallsmart	430	680	2	114	35	1484	65	45	34	D	M
8 000 723	W 80 - 2 kW/1x230V	Wallsmart	430	1000	2	174	33	1542	75	77	43	D	M
8 000 724	W 100 - 2 kW/1x230V	Wallsmart	430	1230	2	228	35	2901	75	95	50	D	L
Domestic products - Indirect													
80 801 200	S 120 - 3 kW/1x230V	Super Standard	580	850	3	169	36	2857	70	112	40	D	L
80 801 400	S 150 - 3 kW/1x230V	Super Standard	580	950	3	215	36	2876	70	142	50	D	L
80 801 600	S 200 - 3 kW/1x230V	Super Standard	580	1260	4	292	36	4609	70	193	62	D	XL
80 801 800	S 300 - 3 kW/1x230V	Super Standard	580	1710	6	423	36	4704	70	280	82	D	XL
8 000 601	SX 150 - 2+(2) kW/1x230V	Super Xpress	580	950	3	324	35	2929	75	143	53	D	L
8 000 602	SX 200 - 3+(3) kW/1x230V	Super Xpress	580	1260	4	294	36	4716	75	193	65	D	XL
8 000 603	SX 300 - 3+(3) kW/1x230V	Super Xpress	580	1710	6	432	34	6288	75	280	85	E	XXL
8 000 402	DA 200 - 3kW/1x230V	Delta Agri	595	1270	4	301	37	4501	75	199	48	D	XL
8 000 404	DA 300 - 3kW/1x230V	Delta Agri	595	1750	5	437	37	4557	75	289	64	D	XL
8 000 406	DA 300 - 3kW/1x400V	Delta Agri	595	1750	5	437	37	4557	75	289	64	D	XL
8 000 801	SC 150 - 3 kW/1x230V + coil 0,8m ²	Super Coil	580	950	3	Boiler ≤ 25 kW	-	-	-	142	52	B	-
8 000 802	SC 200 - 3 kW/1x230V + coil 0,8m ²	Super Coil	580	1260	4	Boiler ≤ 25 kW	-	-	-	190	64	C	-
8 000 803	SC 300 - 3 kW/1x230V + coil 0,8m ²	Super Coil	580	1710	6	Boiler ≤ 25 kW	-	-	-	277	84	C	-
8 000 314	DC 200 - 3kW/1x230V + coil 0,8m ²	Delta Coil	595	1270	5	Inv. HP / Boiler	-	-	-	194	43	A	-
8 000 316	DC 300 - 3kW/1x230V + coil 0,8m ²	Delta Coil	595	1750	6	Inv. HP / Boiler	-	-	-	284	49	A	-
8 000 311	DSC 300 - 3kW/1x230V + coil 0,8m ²	Delta Sun Coil	595	1750	6	Sun ≤ 10m ²	-	-	-	284	49	A	-
8 000 302	DGC 200 - 3kW/1x230V + coil 1,4m ²	Delta Geo Coil	595	1270	4	HP ≤ 10kW	-	-	-	194	43	A	-
8 000 304	DGC 300 - 3kW/1x230V + coil 1,8m ²	Delta Geo Coil	595	1750	6	HP ≤ 12kW	-	-	-	284	49	A	-
8 000 306	DTC 200 - 3kW/1x230V + coil 0,8m ² + 0,8m ²	Delta Twin Coil	595	1270	4	Sun + Boiler	-	-	-	192	56	B	-
8 000 308	DTC 300 - 3kW/1x230V + coil 0,8m ² + 0,8m ²	Delta Twin Coil	595	1750	6	Sun + Boiler	-	-	-	282	68	B	-

OSO Hotwater - ErP information

26.05.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)								
OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Heat-up time Δt 65°C [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]	Volume [L]	Heat loss [W]	Rating ERP	Profile ERP
8 000 266	EPC 300 - 3+9 kW/1/3x230V + coil 0,8m ²	Optima Coil	580	1663	3	HP \leq 12 kW	-	-	-	163/115	52/48	B/B	-
8 000 267	EPC 360 - 3+15 kW/1/3x230V + coil 0,8m ²	Optima Coil	580	1990	7	HP \leq 12 kW	-	-	-	206/134	59/63	B/C	-
8 000 277	EPCI 360 - 3+15 kW/1/3x230V + coil 1,8m ²	Optima Coil Inside	580	1995	5	HP \leq 12 kW	-	-	-	244/97	71/54	C/C	-
8 000 279	EPTC 400 - 3+15 kW/1/3x230V + coil 0,8+0,7m ²	Optima Twin Coil	580	2250	7	HP + Sun	-	-	-	203/179	59/71	B/C	-
8 000 281	EPTRC 400 - 3+9 kW/1/3x230V + coil 1,8+0,8+0,7m ²	Optima Triple Coil	580	2250	5	HP + Sun	-	-	-	240/138	73/58	C/C	-
8 011 202	50 R 50	Accu	430	680	2	Heatsource	-	-	-	49	42	C	-
8 011 205	50 R 100	Accu	430	1170	2	Heatsource	-	-	-	100	59	C	-
8 011 281	50 RE 300 - 15 kW/3x230V	Accu	580	1600	4	Heatsource	-	-	-	282	102	D	-
8 011 201	50RE 100- 9kW/3x400V	Accu	430	1210	2	Heatsource	-	-	-	100	67	C	-
8 011 182	50 RC 300 - coil 2,6m ²	Accu Coil	580	1600	5	Heatsource	-	-	-	268	99	D	-
8 011 312	50 RCE 300 - 15 kW/3x230V + coil 2,6m ²	Accu Coil	580	1600	4	Heatsource	-	-	-	268	105	D	-
Industrial products - direct / indirect													
8 011 106	17R 300	Maxi Turbo	580	1600	-	Heatsource	-	-	-	275	101	D	-
8 011 109	17R 400	Maxi Turbo	580	2085	-	Heatsource	-	-	-	376	127	D	-
8 010 573	17RE 300 - 15 kW/3x230V	Maxi Standard	580	1600	-	84	37	11187	75	280	105	NA	3XL
8 010 579	17RE 400 - 15 kW/3x230V	Maxi Standard	580	2085	-	114	36	11461	75	372	130	NA	3XL
8 010 581	17RED 400 - 15+15 kW/3x230V	Maxi Standard Double	580	2085	-	51	36	11486	75	367	135	NA	3XL
8 011 351	17RTVE 400 - 15kW/3x230V + coil 1,4m ²	Maxi Eco	580	2085	-	HP \leq 10 kW	-	-	-	368	137	E	-
8 010 535	17RVE 300 25KW VVX+ 15KW EL	Maxi Combi	580	1600	-	Boiler \leq 25 kW	-	-	-	271	107	D	-
8 010 541	17RVE 400, 25KW VVX + 15KW EL.	Maxi Combi	580	2085	-	Boiler \leq 25 kW	-	-	-	363	131	E	-
8 160 003	51R 300	Maxi Accu	580	1606	-	Heatsource	-	-	-	275	61	B	-
8 160 004	51R 400	Maxi Accu	580	2085	-	Heatsource	-	-	-	368	82	C	-
8 202 709	81R 180 - 30 kW/3x230V	Universal	595	1270	-	30	-	-	75	168	97	D	-
8 202 713	81R 250 - 45 kW/3x230V	Universal	595	1540	-	24	-	-	75	236	109	D	-
8 202 714	81R 300 - 60 kW/3x230V	Universal	595	1750	-	24	-	-	75	271	120	E	-