

# OSO Hotwater - ErP information

18.10.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)								
OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Heat-up time [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]	Volume [L]	Heat loss [W]	Rating ERP	Profile ERP
<b>Domestic products - Direct electric</b>													
20000051	N 5 (2kW)	Nano	200x234	500	1	0	35	525	60	6	17	A	XXS
8000051	N 5 (3kW)	Nano	200x234	500	1	0	35	525	60	6	17	A	XXS
8000451	W 30	Wally	434	418	1	1	36	520	70	28	25	B	S
8000452	W 50	Wally	434	628	2	1,6	38	1369	70	45	32	C	M
8000453	W 70	Wally	434	836	2	2,3	38	1341	65	66	42	C	M
8000454	W 90	Wally	434	1096	2	3,1	38	2690	65	91	48	C	L
8000455	W 120	Wally	434	1408	3	4,0	38	2719	65	121	53	C	L
80804551	S 120	Saga	580	890	3	2,8	38	1336	70	111	43	C	M
80804552	S 150	Saga	580	950	3	3,6	39	2625	70	143	52	C	L
80804554	S 200	Saga	580	1260	4	4,9	39	2641	70	193	65	C	L
80804556	S 300	Saga	580	1710	6	7,2	39	4325	70	280	85	C	XL
8000652	SX 150	Saga Xpress	580	950	3	5,4	-	-	75	143	53	B	-
8000654	SX 200	Saga Xpress	580	1260	4	4,9	-	-	75	194	65	C	-
8000656	SX 300	Saga Xpress	580	1710	6	7,2	-	-	75	287	85	C	-
8000402	DI 200	Delta Inox	595	1270	4	5,0	37	4501	75	199	48	D	XL
8000404	DI 300 (230V)	Delta Inox	595	1750	5	7,3	37	4557	75	289	64	D	XL
8000406	DI 300 (400V)	Delta Inox	595	1750	5	7,3	37	4557	75	289	64	D	XL
20203800	C 200	Cubix	595x635	1370	4	4,9	37	4490	75	193	59	D	XL
20203900	C 300	Cubix	595x635	1820	5	6,9	39	4338	65	272	82	C	XL

# OSO Hotwater - ErP information

18.10.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)								
OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Heat-up time [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]	Volume [L]	Heat loss [W]	Rating ERP	Profile ERP
<b>Domestic products - Indirect</b>													
8000952	SC 150	Saga Coil	580	950	3	3,6	-	-	75	140	52	B	-
8000954	SC 200	Saga Coil	580	1260	4	4,9	-	-	75	190	64	C	-
8000956	SC 300	Saga Coil	580	1710	6	7,2	-	-	75	283	84	C	-
8000314	DC 200	Delta Coil	595	1270	4	Inv. HP / Boiler	-	-	70	194	43	A	-
8000316	DC 300	Delta Coil	595	1750	5	Inv. HP / Boiler	-	-	70	285	49	A	-
8000302	DGC 200	Delta Geocoil	595	1270	4	HP ≤ 10kW	-	-	70	191	43	A	-
8000304	DGC 300	Delta Geocoil	595	1750	6	HP ≤ 10kW	-	-	70	282	49	A	-
8000306	DTC 200	Delta Twincoil	595	1270	4	Sun + Boiler	-	-	70	190	56	B	-
8000308	DTC 300	Delta Twincoil	595	1750	5	Sun + Boiler	-	-	70	281	68	B	-
8000266	OC 300	Optima Coil	580	1663	3	HP≤12 kW	-	-	75	163/115	52/48	B/B	-
8000267	OC 360	Optima Coil	580	1990	7	HP ≤12 kW	-	-	75	206/134	59/63	B/C	-
8000277	OGC 360	Optima Geocoil	580	1995	5	HP ≤12 kW	-	-	75	244/97	71/54	C/C	-
8000282	OTC 400	Optima Twincoil	580	2238	7	HP + Sun	-	-	75	203/179	59/71	B/C	-
8011202	A 50	Accu	434	597	-	-	-	-	-	48	42	C	-
8011205	A 100	Accu	434	1134	-	-	-	-	-	100	59	C	-
8011281	AS 300	Accu Standard	580	1600	4	Heatsource	-	-	45	282	76	C	-
8011201	AS 100	Accu Standard	430	1210	2	Heatsource	-	-	45	100	67	C	-
8011182	AGC 300	Accu Coil	580	1600	5	Heatsource	-	-	-	268	78	C	-
8011312	AGC 300	Accu Geocoil	580	1600	4	Heatsource	-	-	45	268	83	C	-

## OSO Hotwater - ErP information

18.10.17

Product identification			Dimensions		Product characteristics - ErP (Heat loss according to EN 12897, tapping according to EN 50440)								
OSO no.	Product code	Product series	Dia. [mm]	Height [mm]	Capacity persons	Heat-up time [Hrs]	Energy Efficiency [%]	AEC [kWh/a]	Temp. Setting [°C]	Volume [L]	Heat loss [W]	Rating ERP	Profile ERP
<b>Industrial products - direct / indirect</b>													
8001451	M 300	Maxi	595	1682	-	-	-	-	-	282	81	C	-
8001452	M 400	Maxi	595	2172	-	-	-	-	-	376	85	C	-
8001453	M 600	Maxi	780	1900	-	-	-	-	-	550	119	C	-
8001454	M 1000	Maxi	1000	2100	-	-	-	-	-	885	140	C	-
8001551	MS 300	Maxi Standard	595	1682	-	-	-	-	75	280	83	C	-
8001552	MS 400 (230V)	Maxi Standard	595	2172	-	-	-	-	75	372	90	C	-
8001558	MS 400 (400V)	Maxi Standard	595	2172	-	-	-	-	75	372	90	C	-
8001553	MS 600	Maxi Standard	780	1900	-	-	-	-	75	550	120	C	-
8001554	MS 1000	Maxi Standard	1000	2100	-	-	-	-	75	885	142	C	-
8001852	MGC 400	Maxi Geocoil	595	2172	-	-	-	-	75	363	96	C	-
8001853	MGC 600	Maxi Geocoil	780	1900	-	-	-	-	75	523	118	C	-
8001854	MGC 1000	Maxi Geocoil	1000	2100	-	-	-	-	75	865	141	C	-
8001751	MC 300	Maxi Coil	595	1682	-	-	-	-	75	271	86	C	-
8001752	MC 400	Maxi Coil	595	2172	-	-	-	-	75	363	94	C	-
8001753	MC 600	Maxi Coil	780	1900	-	-	-	-	75	534	119	C	-
8001754	MC 1000	Maxi Coil	1000	2100	-	-	-	-	75	877	142	C	-
8001351	MA 300	Maxi Accu	595	1682	-	-	-	-	-	280	81	C	-
8001352	MA 400	Maxi Accu	595	2172	-	-	-	-	-	379	87	C	-
8001353	MA 600	Maxi Accu	780	1900	-	-	-	-	-	550	119	C	-
8001354	MA 1000	Maxi Accu	1000	2100	-	-	-	-	-	885	140	C	-
8001652	MX 400	Maxi Xpress	595	2172	-	-	-	-	75	367	103	C	-
8001653	MX 600	Maxi Xpress	780	1900	-	-	-	-	75	550	120	C	-
8001654	MX 1000	Maxi Xpress	1000	2100	-	-	-	-	75	885	142	C	-
8202709	E 180	Electra	595	1270	-	0,4	-	-	75	168	70	C	-
8202713	E 250	Electra	595	1540	-	0,4	-	-	75	250	92	C	-
8202714	E 300	Electra	595	1750	-	0,4	-	-	75	271	95	C	-