

Maxi Standard - 17RE (SE) - direct electric



Suitable for medium and larger sized systems

Maxi Standard provides hot water through direct electric heating, integrated in the Maxi Standard's electric box(es). The electric effect can be delivered up to 100 kW, in one or more electric boxes. The electric box is fully built in and insulated.

The pressure vessel is manufactured in stainless steel (up to 1.000 litres), and is designed for pressures of up to 10 bar. The cold water inlet kit, mixing valve kit (if required) and the parallel / series connection kits are assembled directly on the units' front. Contact your supplier for more information regarding the kits. Electric immersion heaters are fitted according to customer's specification, in single or three phase supply. High outputs are available. Immersion elements are controlled by independent thermostats each with an individual safety cut-out. Safety relief valve (P&T) 10bar/99°C is included.

ADVANTAGES

- Stainless steel pressure vessel designed for 10 bar pressure, with 15 kW el. as standard
- All valve kits and connections fits directly onto the front
- Extensive product range up to 10 000 ltrs. Units from 1 500 ltrs upwards has Cu inner lining.

PRODUCT DATA

Guarantee	Tank 10 yrs* - parts 2 yrs
Insulation	Mineral wool
Certification	CE / NEMKO
El. element	5/4" thread
Thermostat	60-90°C (preset 75°C)
Connection kits	Fits onto unit front
P&T safety valve	10 bar / 99°C - included

*Subject to T&C