

Slimline Direct - RD - the slimmest domestic cylinder available



Suited for narrow and tight spaces

The Slimline is the slimmest domestic cylinder available at only 430 mm diameter, making the cylinder ideal for installation in tight spaces. The cylinder is designed with twin immersion heaters for off-peak heating and boost element. Low heat loss comes from OSO ECO Foam insulation. High flow rates provide powerful showers.

The cylinder is floor mounted and is supplied with a wall bracket to stabilize the unit. An external expansion vessel is supplied with its own wall bracket.

Slimline is simple to fit and follows a similar installation technique to the OSO renewable and PowerCyl cylinders. A dedicated secondary return is supplied as standard.

ADVANTAGES

- Lightweight and compact cylinder for easy handling and installation
- Fits in the smallest spaces - only 430 mm diameter
- OSO ECO Foam insulation and 10 year guarantee

PRODUCT DATA

Guarantee	Tank 10 yrs* - parts 2 yrs
Insulation	ECO Foam - water based
Certification	CE / KIWA
El. elements	1" thread
Thermostats	40-70°C (preset 60°C)
Power supply	Dual - separate
Safety valve	10 bar/90-95°C - fitted

*Subject to T&C

Technical Data Fiche

Prod. No.	Product code:	Capacity persons	Weight kg.	DiaxHeight mm.	Th.stat setting °C	Volume L	Volume L at 40°C	Heat loss kWh/d	Heat loss W	Load profile ErP	Efficiency %	Rating ErP
132 6100	15RD 150 -2+2kW/1x240V	2.5	50	ø430x1610	60	143	226	2.3	77	XL	33.65	E